



TITLE  
**PW125.INS.AB**

DRAWN BY  
C.MORRIS

DATE  
28/11/2017

CUSTOMER  
CUSTOMER

**NOTE:**  
All Tanks Direct tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.

ALL DIMENSIONS +/- 5mm  
UNLESS OTHERWISE STATED

**DESCRIPTION:**  
PW125 one piece cold water storage tank  
c/w raised float valve housing to provide an  
AB Air gap

A4

ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
04/10/2017	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	500 x 500 x 500mm
EXTERNAL DIMENSIONS	690 x 690 x 813mm
NOM. CAPACITY	125 Litres
DRY WEIGHT	10 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	1310072
MATERIAL	GRP



SCALE:1:15

SHEET 1 OF 1