



TITLE  
**PW338.INS-2 (AB)**

DRAWN BY **J. Ellison** DATE **06/04/2022**

CUSTOMER **CUSTOMER**

**NOTE:**  
All Tanks Direct tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.

ALL DIMENSIONS +/- 5mm  
UNLESS OTHERWISE STATED

DESCRIPTION:  
**PW338-AB Two piece cold water storage tank suitable for AB Air gaps**

**A4**

ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
16/12/2021	A	FIRST ISSUE

**TANK SPECIFICATION :**

INTERNAL DIMENSIONS	610 x 610 x 910mm
EXTERNAL DIMENSIONS	805 x 805 x 1283mm
NOM. CAPACITY	338 Litres
DRY WEIGHT	25 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	1310072
MATERIAL	GRP

SCALE:1:20 SHEET 1 OF 1