



TITLE  
**PW.2x1.5x1.TIF.AB**

DRAWN BY J. Ellison DATE 01/02/2023

CUSTOMER CUSTOMER

**NOTE:**  
Tanks Direct sectional tanks must be fully supported on a flat, level & continuous foundation which provides structural support to the tank when full to a maximum capacity. It is essential that the installer and/or user refers to the conditions of the installation document prior to the installation of the tank. Under no circumstances should any part of the tank structure be used to provide support to pipework and/or any ancillary items.

ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED

**DESCRIPTION:**  
PW.2x1.5x1.TIF Sectional cold water storage tank c/w raised float valve housing to provide an AB Air gap

A4 ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
24/01/2023	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	2150 x 1650 x 1150mm
EXTERNAL DIMENSIONS	2224 x 1724 x 1710mm
NOM. CAPACITY	4079 Litres
INSULATION THICKNESS	38mm
MATERIAL	Hot press moulded GRP



SCALE:1:30 SHEET 1 OF 1