



TITLE
PW1.5x1x1.5.TIF.AG

DRAWN BY
C.MORRIS DATE
01/02/2023

CUSTOMER
CUSTOMER

NOTE:
 Tanks Direct sectional tanks must be fully supported on a flat, level & continuous foundation which provides structural support to the tank when full to a maximum capacity. It is essential that the installer and/or user refers to the conditions of the installation document prior to the installation of the tank. Under no circumstances should any part of the tank structure be used to provide support to pipework and/or any ancillary items.

ALL DIMENSIONS +/- 5mm
 UNLESS OTHERWISE STATED

DESCRIPTION:
 PW.1.5x1x1.5.TIF Sectional cold water storage tank
 c/w access manway to provide an AG Airgap

A4

ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
25/01/2023	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	1650 x 1150 x 1650mm
EXTERNAL DIMENSIONS	1724 x 1224 x 1845mm
NOM. CAPACITY	3130 Litres
INSULATION THICKNESS	38mm
MATERIAL	Hot press moulded GRP

TANKS DIRECT

SCALE:1:30 SHEET 1 OF 1