



TITLE
PW.3X1X1.5.TIF.DIV.AG (1.5+1.5)

DRAWN BY C.MORRIS DATE 01/02/2023

CUSTOMER CUSTOMER

NOTE:
Tanks Direct sectional tanks must be fully supported on a flat, level & continuous foundation which provides structural support to the tank when full to a maximum capacity. It is essential that the installer and/or user refers to the conditions of the installation document prior to the installation of the tank. Under no circumstances should any part of the tank structure be used to provide support to pipework and/or any ancillary items.

ALL DIMENSIONS +/- 5mm
UNLESS OTHERWISE STATED

A4

DESCRIPTION:
PW.3x1x1.5.TIF.DIV. Sectional cold water storage tank c/w access manways to provide an AG Air gap.

ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
30/01/2023	A	FIRST ISSUE

TANK SPECIFICATION :

INTERNAL DIMENSIONS	3150 x 1150 x 1650mm
EXTERNAL DIMENSIONS	3234 x 1224 x 1845mm
NOM. CAPACITY	5977 Litres
INSULATION THICKNESS	38mm
MATERIAL	Hot press moulded GRP



SCALE:1:35

SHEET 1 OF 1