



TITLE  
PW.3x2x1.5.TIF.DIV.AG

DRAWN BY C.MORRIS DATE 01/02/2023  
CUSTOMER CUSTOMER

**NOTE:**  
Tanks Direct sectional tanks must be fully supported on a flat, level & continuous foundation which provides structural support to the tank when full to a maximum capacity. It is essential that the installer and/or user refers to the conditions of the installation document prior to the installation of the tank. Under no circumstances should any part of the tank structure be used to provide support to pipework and/or any ancillary items.

ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED

**DESCRIPTION:**  
PW.3x2x1.5.TIF.DIV. Sectional cold water storage tank c/w access manways to provide an AG Air gap.

A4 ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
26/01/2023	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	3150 x 2150 x 1650mm
EXTERNAL DIMENSIONS	3224 x 2234 x 1851mm
NOM. CAPACITY	11,174 Litres
INSULATION THICKNESS	38mm
MATERIAL	Hot press moulded GRP



SCALE:1:40 SHEET 1 OF 1