



TITLE
FW 3x1x2.TIF.DIV.AG (1.5+1.5)

NOTE:
Tanks Direct sectional tanks must be fully supported on a flat, level & continuous foundation which provides structural support to the tank when full to a maximum capacity. It is essential that the installer and/or user refers to the conditions of the installation document prior to the installation of the tank. Under no circumstances should any part of the tank structure be used to provide support to pipework and/or any ancillary items.

DESCRIPTION:
PW.3x1x2.TIF.DIV. Sectional cold water storage tank c/w access manways to provide an AG Air gap.

DATE	VERSION	NOTES
27/01/2023	A	FIRST ISSUE

TANK SPECIFICATION :

INTERNAL DIMENSIONS	3150 x 1150 x 2150mm
EXTERNAL DIMENSIONS	3234 x 1224 x 2345mm
NOM. CAPACITY	7788 Litres
INSULATION THICKNESS	38mm
MATERIAL	Hot press moulded GRP



DRAWN BY C.MORRIS DATE 01/02/2023

CUSTOMER CUSTOMER

ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED

A4

ALL DIMENSIONS IN MM - DO NOT SCALE

SCALE:1:40

SHEET 1 OF 1