

Energy Management Solutions

UK & Ireland



TrolleyMaster®

Handy and universal mobile tank for Diesel and AdBlue® distribution in any terrain

Available capacities:
60 & 100 L



TrolleyMaster AdBlue®

TrolleyMaster Diesel

Versatile uses



Opportunities with Hire Companies



Marine



All terrain vehicles



Long journeys



Roadside assistance



Forklifts



Landscape/
Ground Maintenance



Repair equipment



Generators



Plant/
Construction



Agriculture
machinery



Forestry

kingspan.com



TrolleyMaster®

Discover the benefits of handy TrolleyMaster mobile tanks



Mobility

Safely transport diesel/ AdBlue® directly to machines, including boats and equipment operating in difficult terrain



Trustworthy Quality

Durable construction, corrosion free and weatherproof



Saving Time and Resources

Mobile tanks are compact and perfect in the agricultural, construction or forestry industry, because they let you avoid equipment downtime during work



Peace of Mind

2 years guarantee on the tank



Off-road rubber wheels

Two solid rubber wheels with a diameter of 250 mm allow for transporting the tank.



Dedicated nozzle pocket

Pocket collects liquid drops from the nozzle and protects the nozzle during tank transport. It can be easily unscrewed and cleaned.



Groove for delivery hose

The profiled groove makes it possible to wrap the hose around the tank while on the move.



Comfort of refueling

An efficient pump with battery clamps allows you to quickly dispense diesel/AdBlue®.



Ergonomic handle

Comfortable, profiled handle provides a secure grip when pulling and lifting the tank.



Ball valve

Ball valve protects against liquid leakage from the product during transport.

Equipment

- | | |
|---|--|
| 1. TrolleyMaster tank | 8. 12 V DC or 24 V DC pump to choose |
| 2. Groove for wrapping the delivery hose during transport | 9. Flexible delivery hose 3 m |
| 3. Nozzle pocket | 10. 3/4" ball valve |
| 4. Automatic nozzle with a swivel | 11. Profiled corners for fastening straps |
| 5. Transport non-slip handles | 12. Solid rubber wheels with a Ø 250 mm diameter |
| 6. Battery clamps | 13. K24 digital flowmeter (optional) |
| 7. Fuel cap with breathing valve | |

Dimensions

		TrolleyMaster® 60	TrolleyMaster® 100
Capacity		60 Litres/13 Gallons	100 Litres/22 Gallons
Dimensions	Length	380 mm	380 mm
	Width	380 mm	440 mm
	Height	905 mm	1130 mm

For more information about TrolleyMaster:

UK: Tel.: **+44 (0) 28 3836 4444** Email: **tankinfo@kingspan.co.uk**

IE: Tel.: **+353 (0) 42 969 0022** Email: **tankinfo@kingspan.ie**

We take every care to ensure that the information in this document is accurate at the point of publication. Dimensions may vary within a small parameter due to manufacturing process variations or environmental conditions. All images are for illustration purposes only and, along with dimensions, should not be taken as binding. The actual product may vary and aspects such as equipment specification/colour may differ. To ensure you are viewing the most recent and accurate product information, please visit www.kingspan.com
 ©Kingspan and the Lion Device are Registered Trademarks of the Kingspan Group in the UK, Ireland and other countries.
 All rights reserved. Registered in Country No.NI017631. Registered Office: 180 Gilford Road, Portadown, Co. Armagh, BT635LF. VAT GB412 5124 03

