

**Notes:**

- Pumpwell delivered with pump & floats not installed to avoid damage in transit.
- Pumps to be coupled to chains with shackles supplied in lifting chain which is connected to the unistrut assembly.
- Read operating and installation guidelines before installing.


Case Diameter	Outlet Invert 'C'	Case Depth 'B'		Inlet Invert 'A' - Standard		Inlet Size 'E'
		20 (2.0m)	25 (2.5m)	10 (1.0m)	15 (1.5m)	
10 (1.0m)	0.6m	•		•		110mm
			•		•	160mm

Please check with Kingspan Water & Energy for the latest Issue of the drawing				
Issue	Date	Drawn By	Approved By	Description
02	19/12/2022	TGY		ECN 1641 - Access Size Added
01	19/02/2010	S.Gill		Initial Release

LN Number :	Tolerance (unless stated) :
Finish :	Thickness :
Weight :	Surface Area : m <sup>2</sup>
Modelled By : Author	Material : PE

**Drawing : DS1063P** Page 1 of 1  
 Pump Chamber Ø1.0 Sewage

All Dimensions In mm Scale: Do Not Scale



Kingspan Water & Energy reserve the right to alter the details of this drawing without prior notice. This drawing is copyright and may not be reproduced or used without the written permission of Kingspan Water & Energy

