



TITLE	
PW2001.INS (AG)	
DRAWN BY	DATE
J. Ellison	06/04/2022
CUSTOMER	
CUSTOMER	

NOTE:
All Tanks Direct tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.
ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED

DESCRIPTION:
PW2001-AG One piece cold water storage tank suitable for AG/AF Air gaps
A4
ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
14/12/2021	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	1000 x 1000 x 2000mm
EXTERNAL DIMENSIONS	1180 x 1180 x 2093mm
NOM. CAPACITY	2000 Litres
DRY WEIGHT	150 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	1310072
MATERIAL	GRP
