



NOTES:-

1. BIODISC TANK & COVER ARE MANUFACTURED IN GLASS REINFORCED POLYESTER (GRP) COVER IS FINISHED IN GREEN TO BS 4800 TINT 12B25
2. FOR DESLUDGING PROCEDURE SEE MAINTENANCE HANDBOOK.
3. ELECTRICAL SUPPLY- 240 VOLTS, 2 AMPS, SINGLE PHASE. (THREE PHASE OPTIONAL.) CONTROL PANEL SUPPLIED.
4. BIODISC MUST BE LIFTED BY THE 4 LIFTING LUGS PROVIDED. USE SLINGS.
5. 3 DRAIN INVERTS AVAILABLE. DIMENSIONS ON DRAWING.
6. FOR INSTALLATION, MAINTENANCE & DESLUDGE DETAILS REFER TO 015122, 013103, P00129.
7. THIS DRAWING IS ALSO AVAILABLE ON OUR WEBSITE [WWW.KINGSPANENV.COM](http://www.kingspanenv.com)

	DRY WEIGHT	
600mm INVERT	650	Kg
900mm INVERT	700	
1100mm INVERT	750	

ISSUE	DATE	BY/APP	INITIAL	ISSUE	DESCRIPTION
1	30.03.11	JM/CD		INITIAL ISSUE	
2	07.03.16	T.K.		CC1298 - 900mm Invert introduced	

This drawing is copyright and may not be reproduced or used without the written permission of Kingspan Environmental. KINGSKAN RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE.

Kingspan
Environmental

ALL DIMENSIONS ARE IN MILLIMETRES - DO NOT SCALE

TITLE
BC BIODISC
GENERAL
DIMENSIONS
CUSTOMER DRAWING

SCALE	1:10	SHEET SIZE	A1
DRAWING No.	DS0456P	ISSUE	2