


IMPORTANT INVERT LEVEL NOTE (RIBBED TANKS ONLY):
 The inlet and outlet Invert Level(IL) shown on this drawing is to internals of the shell unless otherwise stated.
 For Invert level to the outside of the shell ribs, see the conversion below:
 Ø1.0m, 1.2m, 1.5m, 1.8m, 2.5m IL+50mm ('X')
 Ø3.0m, 4.0m IL+75mm ('X')

TANKS SUPPLIED WITH LOOSE SHAFTS DO NOT COME SUPPLIED WITH A FIXING KIT.
 THIS IS THE RESPONSIBILITY OF THE SITE CONTRACTOR.



REV.	DATE	BY	CHKD.	PB	RP	ISSUED FOR INFORMATION	DESCRIPTION		
1	23.03.09	RU					THIS DRAWING IS THE PROPERTY OF CONDER SOLUTIONS Ltd. AND IS NOT TO BE COPIED IN PART OR WHOLE WITHOUT WRITTEN PERMISSION		
A3	DO NOT SCALE IF IN DOUBT ASK ALL DIMENSIONS IN MM		GENERAL TOLERANCES (unless noted otherwise)		GRP FABRICATED MACHINED	LINEAR	± 5mm ± 2mm ± 0.5mm	ANGLE	±0.5° ±0.2° ±0.1°

TITLE	DRAWN BY	CHKD.	PB	APPD.	RP	SCALE	DRAWING No.	REVISION
ASP16 SEWAGE TREATMENT PLANT	RU					NTS	ASP16 SALES	1
	DATE	DATE	DATE	DATE				
	23.03.09	23.03.09	23.03.09					