



TITLE  
**PW680.INS-2.AG**

DRAWN BY  
C.MORRIS

DATE  
27/11/2017

CUSTOMER  
CUSTOMER

**NOTE:**  
All Tanks Direct tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.

ALL DIMENSIONS +/- 5mm  
UNLESS OTHERWISE STATED

**DESCRIPTION:**  
PW680-2 piece cold water storage tank suitable for AG/AF Air gap

A4

ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
18/09/2017	A	FIRST ISSUE

**TANK SPECIFICATION :**

INTERNAL DIMENSIONS	1220 x 915 x 610mm
EXTERNAL DIMENSIONS	1395 x 1087 x 649mm
NOM. CAPACITY	680 Litres
DRY WEIGHT	40 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	1310072
MATERIAL	GRP

SCALE:1:20

SHEET 1 OF 1