



TITLE		NOTE: All Tanks Direct tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.
PW650.INS-2.AB.4		
DRAWN BY	DATE	
C.MORRIS	19/12/2017	
CUSTOMER	ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED	
CUSTOMER	A4	

DESCRIPTION:		TANK SPECIFICATION :
PW650-2 piece cold water storage tank c/w raised float valve housing to provide an AB Air gap		
ALL DIMENSIONS IN MM - DO NOT SCALE		

DATE	VERSION	NOTES
18/09/2017	A	FIRST ISSUE

INTERNAL DIMENSIONS	1067 x 610 x 1000mm
EXTERNAL DIMENSIONS	1255 x 805 x 1030mm
NOM. CAPACITY	650 Litres
DRY WEIGHT	43 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	1310072
MATERIAL	GRP

SCALE: 1:15

SHEET 1 OF 1