



• Single Pump Packaged Booster Set and CAT5 Break Tank.

Fixed Speed Pressure Pump - Variable speed optional upon request. Pre-assembled for easy installation. Wet/Pressure tested prior to despatch.

Quiet operation, less than 50 decibels. Compact design, narrow width ideal for access through doorways. WRAS Approved water storage tank manufactured from GRP with 25mm insulation. WRAS Approved $\frac{3}{4}$ " High flow ball valve fitted.

Low Water Level Protection.

WRAS Approved fully adjustable system pressure reducing valve fitted. Maximum allowable static head 12 metres.

Rev	Date Description									
THIRD ANGLE PROJECTION										
								2	1	
AN DIS	D MA	Y NOT BE SED TO A	S CONFIDI USED, CONYONE WI OF D.P. 8	OPIED OR			L			
PRODUCT CODE					PRODUCT DESCRIPTION					
	PT CA	AT5 251			BOOSTE	R SET RA	NG	Ξ		
DF					Approved By:	J.F.	REV	1	SHEET 1	OF
DF Drawr	ו By:	R.U.	Checked By:	J.F.	Approved by.			1 1		
Drawr	n By: n Date:	R.U. 09/03/2021	Checked By: Checked Date:		Approved By: Approved Date:	09/03/2021	SIZE	A3	SCALE 1:5	